

Ficha técnica do produto



HF 100 C

Limas Rotativas



Propriedades: Lima rotativa cilíndrica com ponta esférica - Denominação conforme DIN 8032:

WRC Vantagens: Para trabalhos de superfícies, contornos e raios

Diâmetro in mm	Comprimento in mm	Diâmetro do eixo in mm	Altura in mm	Segmento	Max. RPM in rpm	Cat.number
6.0	50.0	6.0	18.0	2.0	65000.0	295686
6.0	50.0	6.0	18.0	3.0	65000.0	295688
6.0	50.0	6.0	18.0	6.0	65000.0	295694
8.0	63.0	6.0	19.0	6.0	55000.0	295713
9.6	63.0	6.0	19.0	3.0	55000.0	295725
9.6	63.0	6.0	19.0	6.0	55000.0	295727
12.7	64.0	6.0	19.0	6.0	35000.0	295741
12.7	70.0	6.0	25.0	2.0	35000.0	295747
12.7	70.0	6.0	25.0	3.0	35000.0	295750
12.7	70.0	6.0	25.0	6.0	35000.0	295753
16.0	70.0	6.0	25.0	6.0	25000.0	295763
3.0	38.0	3.0	14.0	2.0	100000.0	295649
3.0	38.0	3.0	14.0	6.0	100000.0	295654
6.3	44.0	3.0	12.7	6.0	65000.0	295673